PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2002-226708

(43)Date of publication of application: 14.08.2002

(51)Int.CI.

C08L 83/06 C08K 5/07 C08K 5/17 C08K 5/541 C08K 9/06

3/10

C09K

(21)Application number: 2001-021815

(71)Applicant: THREE BOND CO LTD

TOYOTA MOTOR CORP

(22)Date of filing:

30.01.2001

(72)Inventor: KAGOSAKI TATSUYA

TASHIRO HIROSHI KICHIJIMA KAZUYA ONOUCHI HIROYUKI

(54) ROOM TEMPERATURE-CURABLE SEALING MATERIAL COMPOSITION USED FOR AUTOMOBILES

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a room temperature-curable sealing material composition of a condensation curing type used for automobiles that has excellent quick curing properties and curing properties in the depth, as well as engine oil resistance, long-life coolant resistance and water resistance.

SOLUTION: This room temperature-curable sealing material composition used for automobiles comprises (A) 100 pts.wt. of a dimethylpolysiloxane having both terminals of the molecular chain blocked with hydroxy groups, and having a viscosity at 25° C of 1,000–100,000 mPa.s. (B) 2–15 pts.wt. of a silane compound having a general formula: CH2=CHSi(O-N=CR1R2)3 (wherein R1 and R2 are each, same or different, a 1–6C monovalent hydrocarbon group) or a partially hydrolyzed product thereof, (C) a ketone compound in an amount wherein 0.001–1.0 mol of a reactive carbonyl group is present per 100 pts.wt. of (A), (D) an amine compound having a primary amino group wherein 0.001–1.0 mol of the primary amino group is present per 100 pts.wt. of (A), and (E) 5–150 pts.wt. of zinc oxide having a surface treated to provide a hydrophobia property.

LEGAL STATUS

[Date of request for examination]

26.02.2003

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision